



- NOTES:
1. DISPLAY TYPE: FSTN
 2. VIEWING DIRECTION: 6:00
 3. POLARIZER MODE: TRANSFLECTIVE/POSITIVE
 4. DRIVE METHOD: 1/49 DUTY 1/8 BIAS
 5. VDD=3.0V VDP=8.4V
 6. OPERATING TEMP.: -20°C~+70°C
 7. STORAGE TEMP.: -30°C~+80°C
 8. CONTROLLER: TL0324SF9
 9. CONNECTION: FPC
 10. BACKLIGHT TYPE: LED B/L(WHITE LED)
 11. UNMARKED TOLERANCE: ±0.3mm
 12. CONTROL DIMENSION MASK TO BE:
 13. REQUIREMENTS ON ENVIRONMENTAL PROTECTION SAMSUNG

1	A	11	DB4
2	NC	12	DB3
3	NC	13	DB2
4	K	14	DB1
5	VDD	15	DB0
6	C68	16	RD
7	GND	17	WR
8	DB7	18	RS
9	DB6	19	RES
10	DB5	20	CS1

⚠	G-3: ADD THE RIB ON THE LIGHT GUIDE
	G-2: CHANGE REMOVE TAPE DIMENSION

MULTI-INNO TECHNOLOGY CO.,LTD		
DRAWN BY:	TITLE: MI12848A-2	
CHECKED BY:	DWG NO: G-3	SCALE:
APPROVED BY:	DWG NAME: MI12848A-2	UNT: mm
CONFIRMED BY:		SHEET NO: 1 OF 1