



PIN CONNECTION

NO	SYMBOL
1	/CS1
2	/RESET
3	A0
4	/WR
5	/RD
6	D0
7	D1
8	D2
9	D3
10	D4
11	D5
12	D6(SCL)
13	D7(SI)
14	VDD
15	VSS
16	VOUT
17	CAP3N
18	CAP1P
19	CAP1N
20	CAP2N
21	CAP2P
22	V1
23	V2
24	V3
25	V4
26	V5

DETAIL A



DISPLAY PATTREN



NOTES:

1. DISPLAY TYPE: STN YELLOW-GREEN MODE, TRANSFLECIVE/POSITIVE.
2. DRIVE METHOD: 1/64DUTY, 1/9BIAS, VOP=9.8V, VDD=3.3V
3. VIEWING DIRECTION: 6 O'CLOCK.
4. IC DRIVER: SPLC501C.
5. OPERATING TEMP: -20°C ~ 70°C.
6. STORAGE TEMP: -30°C ~ 80°C.
7. LED BACKLIGHT: YELLOW EDGE LEDA-LEDK=4.2V.
8. ALL UNMARKED TOLERANCES: ±0.3.
9. RoHS COMPLIANT.

CUSTOMER APVL		DATE	
DRAWN		SCALE	TITLE
DFTG CHK		UNIT	MODULE
ENGR CHK		mm	MODEL
APPROVAL		MI12864A2-G	
DWG NO		PAGE	
01		1/6	

--	增加尺寸标注
01	FPC厚度由0.09改为0.14
VERSION	MODIFYCONTENT

MULTI-INNO TECHNOLOGY CO.,LTD.