



DETAIL:A
SCALE:1:30

- NOTES:
1. DISPLAY TYPE:4K CSTN
 2. VIEWING DIRECTION: 6:00
 3. POLARIZER MODE:TRANSMISSIVE/NEGATIVE
 4. MAIN LCD CONTROLLER: UC1681
 5. DRIVE METHODD: DUTY 1/68,BIAS 1/7
 6. VDD=2.8V VOP=10.9V
 7. BACKLIGHT: 1CHIP-WHITE LED
 8. OPERATING TEMP.: -20°C -- +70°C
 9. STORAGE TEMP.: -30°C -- +80°C
 10. UNMARKED TOLERANCE:±0.3
 11. MEANS IMPORTANT DIMENSION
 12. REQUIREMENT ON ENVIRONMENTAL PROTECTION:ROHS

PIN DESCRIPTION

NO.	SYMBOL
1	LED_A
2	LED_K
3	/CS0
4	/RESET
5	CD
6	WR0
7	WR1
8	DB7
9	DB6
10	DB5
11	DB4
12	DB3(SDA)
13	DB2
14	DB1
15	DB0(SCK)
16	VSS
17	VDD
18	BM0
19	BM1
20	VOUT

MULTI-INNO TECHNOLOGY CO.,LTD.

DRAWN BY:	TITLE: MI9867DK	
CHECKED BY:	DWG NO: G-1	
APPROVED BY:	DWG NAME:	UNIT: mm
CONFIRMED BY:		SHEET NO: 1 OF 1

G-1		7/5-06
VER	DESCRIPTION	DATE