



NOTES:

- 1.DISPLAY TYPE: TFT
- 2.VIEING DIRECTION: 6:00
- 3.LCD DRIVE IC: ST7787
- 4.POLARIZER MODE: TRANSMISSIVE/POSITIVE
- 5.DRIVE METHOD: 1/320 DUTY
- 6.VDD: 2.8V
- 7.BACKLIGHT: 4-CHIP LED PARALLEL
- 8.OPERATING TEMP: -20°C -- 70°C
- 9.STORAGE TEMP: -30°C -- 80°C
- 10.UNMARKED TOLERANCE: ±0.20
- 11.CONTROL DIMENSIONS:
- 12.REQUIREMENTS ON ENVIRONMENTAL PROTECTION: RoHS

PIN	SYMBOL
1	NC
2	LED_A
3	LED_K1
4	LED_K2
5	LED_K3
6	LED_K4
7	VDD
8	VCC
9	GND
10	RESET
11	CS
12	RS
13	WR
14	RD
15	DB0
16	DB1
17	DB2
18	DB3
19	DB4
20	DB5
21	DB6
22	DB7
23	DB8
24	DB9
25	DB10
26	DB11
27	DB12
28	DB13
29	DB14
30	DB15
31	DB16
32	DB17
33	IM0
34	IM1
35	GND
36	X+
37	Y-
38	X-
39	Y+
40	NC

MULTI-INNO TECHNOLOGY CO.,LTD.

DRAWN BY:	TITLE: MI0240HT	
CHECKED BY:	DWG NO: G-1	
APPROVED BY:	DWG NAME:	SCALE: UNIT: mm
CONFIRMED BY:	SHEET NO: 1 OF 1	

REV	DESCRIPTION	DATE