



PIN ASSIGNMENT:

1	GND	12	D5
2	VDD	13	D6
3	VADJ	14	D7
4	RS	15	CS
5	WR	16	RST
6	RD	17	VEE
7	D0	18	NC
8	D1	19	NC
9	D2	20	NC
10	D3		
11	D4		

NOTES:

1. DISPLAY TYPE: FSTN
2. VIEWING DIRECTION: 6:00(WIDE VIEWING DIRECTION)
3. POLARIZER MODE: TRANSMISSIVE/NEGATIVE
4. LCD OPERATING VOLTAGE: 21.6V, LOGIC VOLTAGE:5.0V
5. DRIVE METHOD: 1/240 DUTY 1/14 BIAS
6. OPERATING TEMP.: -20° C~+70° C
7. STORAGE TEMP.: -30° C~+80° C
8. Controller: RA8806 Driver:NT7701 (SBC)+NT7702(COM)
9. BACKLIGHT:LEDS(WHITE 10V 60mA (TYPE))
10. BEZEL MATERIAL IS SUS430
11. **UNMARKED TOLERANCES:** ±0.3
12. CONTROLLED DIMENSION MASK
13. REFERENCE DIMENSION MASK ()
14. INCLUDING DC-DC AND TEMPERATURE COMPENSATE CIRCUIT
15. REQUIREMENTS FOR ENVIRONMENTAL PROTECTION:ROHS