


Pin Description

Pin	Name		
1	GND		
2	IM0		
3	IM1		
4	FMARK		
5	NC		
6	DB17	21	DB3
7	DB16	22	DB2
8	DB15	23	DB1
9	DB14	24	DB0
10	DB13	25	/CS
11	DB12	26	RS
12	DB11	27	/WR
13	DB10	28	/RD
14	DB9	29	/RESET
15	DB8	30	VCI
16	IOVCC	31	GND
17	DB7	32	LED+
18	DB6	33	GND
19	DB5	34	LED-
20	DB4	35	GND



NOTES:

1. DISPLAY TYPE: TFT, TRANSMISSIVE, NORMALLY BLACK.
2. OPERATING VOLTAGE: IOVCC/VCI=2.8V.
3. VIEWING DIRECTION: FULL VIEWING ANGLE.
4. IC DRIVER: ILI9341V.
5. OPERATING TEMP: -20°C ~ 70°C.
6. STORAGE TEMP: -30°C ~ 80°C.
7. LED BACKLIGHT: 4-CHIP WHITE LED, If=20mA, Vf=12.8V.
8. SURFACE LUMINANCE: 300cd/m²(MIN).
9. TOP POLARIZER SURFACE TREATMENT: ANTI-GLARE.
10. GENERAL TOLERANCE: ±0.2.
11. RoHS COMPLIANT.

VER.	REVISED DESCRIPTION	DATE
01	FIRST ISSUE	2015.10.10

MULTI-INNO TECHNOLOGY CO.,LTD.

DRAWN BY:	CAROL 2015.10.10	SCALE :	1/1	MODULE P/N:	MI0240AFT-1
CHECKED BY:		UNIT:	mm	DESCRIPTION:	TFT MODULE
APPROVED BY:					
VERSION NO:	01				