



NOTES:

1. DISPLAY TYPE: TFT, TRANSMISSIVE, NORMALLY WHITE.
2. OPERATING VOLTAGE: VCC=3.3V.
3. VIEWING DIRECTION: 12 O'CLOCK.
4. OPERATING TEMP: -20°C ~ 70°C.
5. STORAGE TEMP: -30°C ~ 80°C.
6. SURFACE LUMINANCE: 300cd/m²(TYP).
7. TOP POLARIZER SURFACE TREATMENT: ANTI-GLARE.
8. USER HOLE ROTATIONAL TORQUE: 4kgf-cm.
9. LVDS TYPE: CN1
10. LED POWER CONNECTOR TYPE: STM MSB24038P5 OR EQUIVALENT
11. GENERAL TOLERANCE: ±0.2.
12. RoHS COMPLIANT.

MULTI-INNO TECHNOLOGY CO.,LTD.			
DRAWN BY:	CAROL 2015.05.07	SCALE : 1/1	MODULE P/N:
CHECKED BY:		UNIT:	MI1500HT-6
APPROVED BY:		mm	DESCRIPTION:
VER.	FIRST ISSUE	2015.05.07	TFT MODULE
	REVISED DESCRIPTION	DATE	VERSION NO: 01