


BENDING DIAGRAM FOR REFERENCE



BACKLIGHT CIRCUIT DIAGRAM

PIN DESCRIPTION	
PIN	SYMBOL
1	LEDA
2	GND
3	RESET
4	RS
5	SDA
6	SCL
7	VDD
8	CS

NOTES:

1. DISPLAY TYPE: TFT, TRANSMISSIVE, NORMALLY BLACK
2. OPERATING VOLTAGE: VDD=2.8V
3. VIEWING DIRECTION: FULL VIEWING ANGLE
4. IC DRIVER: ST7789V2
5. OPERATING TEMP.: -20°C ~ 70°C
6. STORAGE TEMP.: -30°C ~ 80°C
7. LED BACKLIGHT: 1-CHIP WHITE LED, If=20mA, Vf=2.9~3.1V
8. TOP POLARIZER SURFACE TREATMENT: ANTI-GLARE
9. SURFACE LUMINANCE: 400CD/M²(TYP)
10. MATED CONNECTOR: FH19SC-08S-0.5SH
11. GENERAL TOLERANCE: ±0.2MM
12. ROHS COMPLIANT

		MULTI-INNO TECHNOLOGY CO., LTD.		
		DRAWN BY: CAROL 2019.07.15 CHECKED BY:	 SCALE : 1/1	MODULE P/N: MI0114AT-1
01 FIRST ISSUE VER. REVISED DESCRIPTION	CAROL 2019.07.15 REVISER DATE	APPROVED BY: VERSION NO: 01	UNIT: mm SHEET NO.: 1/1	DESCRIPTION: TFT MODULE

01	FIRST ISSUE	CAROL	2019.07.15
VER.	REVISED DESCRIPTION	REVISER	DATE