



PIN DESCRIPTION	
PIN	SYMBOL
1	GND
2	LEDK
3	LEDA
4	GND
5	RESET
6	AO
7	SDA
8	SCK
9	VCC
10	IOVCC
11	CS
12	GND

- NOTES:
1. DISPLAY TYPE: TFT, TRANSMISSIVE, NORMALLY WHITE
 2. OPERATING VOLTAGE: VCC=2.8V (TYP.)
 3. VIEWING DIRECTION: 6:00 O'CLOCK
 4. DRIVER IC: ST7735S
 5. OPERATING TEMP.: -20°C ~ 70°C
 6. STORAGE TEMP.: -30°C ~ 80°C
 7. LED BACKLIGHT: 2-CHIP WHITE LED, IF=15mA, VF=6.4V.
 8. SURFACE LUMINANCE: 320CD/M² (TYP.)
 9. TOP POLARIZER SURFACE TREATMENT: ANTI-GLARE
 10. THE SINGLE LAYER AREA OF FPC IS BENDABLE AND THE BENDING RADIUS MUST BE NOT LESS THAN 1.5MM
 11. GENERAL TOLERANCE: ±0.2MM
 12. ROHS COMPLIANT



PIXEL DETAIL (SCALE 40:1)



BACKLIGHT CIRCUIT DIAGRAM

		MULTI-INNO TECHNOLOGY CO., LTD.		
				DRAWN BY: RITA 20211203
CHECKED BY:	SCALE : 1/1	APPROVED BY:	UNIT: mm	DESCRIPTION: TFT MODULE
VER. 01	FIRST ISSUE	RITA 2021.12.03	VERSION NO: 01	SHEET NO.: 1/1

01	FIRST ISSUE	RITA	2021.12.03
VER.	REVISED DESCRIPTION	REVISER	DATE