



PIN DESCRIPTION	
PIN	SYMBOL
1	LEDA
2	LEDK1
3	LEDK2
4	LEDK3
5	LEDK4
6	GND
7	VCC
8	GND
9	SDA
10	SCL
11	D/C
12	CS
13	RESET

NOTES:

1. DISPLAY TYPE: TFT, TRANSMISSIVE, NORMALLY BLACK
2. OPERATING VOLTAGE: VCC=2.8V (TYP.)
3. VIEWING DIRECTION: FULL VIEWING ANGLE
4. DRIVER IC: ST7789V2
5. OPERATING TEMP.: -20°C ~ 70°C
6. STORAGE TEMP.: -30°C ~ 80°C
7. LED BACKLIGHT: 4-CHIP WHITE LED, IF=60mA, VF=3.2V
8. SURFACE LUMINANCE: 230CD/M² (TYP.)
9. TOP POLARIZER SURFACE TREATMENT: ANTI-GLARE
10. THE SINGLE LAYER AREA OF FPC IS BENDABLE AND THE BENDING RADIUS MUST BE NOT LESS THAN 1.5MM
11. GENERAL TOLERANCE: ±0.3MM
12. ROHS COMPLIANT



PIXEL DETAIL



BACKLIGHT CIRCUIT DIAGRAM

MULTI-INNO TECHNOLOGY CO., LTD.			
DRAWN BY:	CAROL	2021.11.17	MODULE P/N:
CHECKED BY:			MIO200AET-1
VER.	01	FIRST ISSUE	DESCRIPTION:
REVISER	CAROL	DATE	TFT MODULE
DATE	2021.11.17	VERSION NO:	01
UNIT:	mm	SHEET NO.:	1/1