



FPC BENDING REFERENCE DIAGRAM



LED CIRCUIT DIAGRAM



PIXEL DETAIL (SCALE 40:1)

- NOTES:
1. DISPLAY TYPE: TFT, TRANSMISSIVE, NORMALLY WHITE
 2. OPERATING VOLTAGE: VCC=IOVCC=2.8V (TYP.)
 3. VIEWING DIRECTION: 6 O'CLOCK
 4. DRIVER IC: ILI9341V
 5. OPERATING TEMP.: -20°C ~ 70°C
 6. STORAGE TEMP.: -30°C ~ 80°C
 7. LED BACKLIGHT: 4-CHIP WHITE LED, IF=60mA, VF=3.2V
 8. SURFACE LUMINANCE: 230CD/M² (TYP.)
 9. TOP POLARIZER SURFACE TREATMENT: GLARE
 10. GENERAL TOLERANCE: ±0.2MM
 11. ROHS COMPLIANT

PIN DESCRIPTION	
PIN	SYMBOL
1	GND
2	GND
3	LEDA
4	LEDK1
5	LEDK2
6	LEDK3
7	LEDK4
8	NC(YU)
9	NC(XL)
10	NC(YD)
11	NC(XR)
12	RST
13	FMARK
14	WR
15	RD
16	RS
17	CS
18	VCC
19	IOVCC
20	DB0
21	DB1
22	DB2
23	DB3
24	DB4
25	DB5
26	DB6
27	DB7
28	GND

MIT MULTI-INNO TECHNOLOGY CO., LTD.

DRAWN BY: RITA	2016.11.11		MODULE P/N:
CHECKED BY:		SCALE : 1/1	MIO200WT-2
APPROVED BY:		UNIT: mm	DESCRIPTION:
VERSION NO: 01		SHEET NO.: 1/1	TFT MODULE

01	FIRST ISSUE	RITA	2016.11.11
VER.	REVISED DESCRIPTION	REVISER	DATE