


NOTES:

1. DISPLAY TYPE: TFT, REFLECTIVE WITH SLIGHT TRANSMISSIVE, NORMALLY BLACK
2. OPERATING VOLTAGE: VDD1=3.2V, VDD2=5.0V (TYP.)
3. VIEWING DIRECTION: FULL VIEWING ANGLE
4. DRIVER IC: -
5. OPERATING TEMP.: -20°C ~ 70°C
6. STORAGE TEMP.: -30°C ~ 80°C
7. LED BACKLIGHT: -
8. SURFACE LUMINANCE: -
9. TOP POLARIZER SURFACE TREATMENT: GLARE
10. GENERAL TOLERANCE: ±0.2MM
11. ROHS COMPLIANT

PIN DESCRIPTION	
PIN	SYMBOL
1	VDD2
2	NC
3	GSP
4	GCK
5	GEN
6	INTB
7	VB
8	VA
9	VDD1
10	VSS
11	BSP
12	BCK
13	R[0]
14	R[1]
15	G[0]
16	G[1]
17	B[0]
18	B[1]
19	NC
20	VCOM
21	NC

 MULTI-INNO TECHNOLOGY CO., LTD.

DRAWN BY:	CAROL 2021.11.15		MODULE P/N:
CHECKED BY:		SCALE : 1/1	MIO213BT-1
APPROVED BY:		UNIT: mm	DESCRIPTION:
VERSION NO:	01	SHEET NO.: 1/1	TFT MODULE

01	FIRST ISSUE	CAROL	2021.11.15
VER.	REVISED DESCRIPTION	REVISER	DATE