



PIN ASSIGNMENT	
PIN	SYMBOL
1	GND
2	LEDK
3	LEDA
4	VDD
5	IOVCC
6	RESET
7	CS
8	SCLK
9	SDA0
10	SDA1
11	SDA2
12	SDA3
13	GND
14	TE

NOTES:

1. DISPLAY TYPE: 2.66", TFT, TRANSMISSIVE, NORMALLY BLACK
2. OPERATING VOLTAGE: VDD=2.8V, IOVCC=1.8V/2.8V
3. VIEWING DIRECTION: FULL VIEWING ANGLE
4. DRIVER IC: NV3007
5. OPERATING TEMP: -20°C ~ 70°C
6. STORAGE TEMP: -30°C ~ 80°C
7. SURFACE LUMINANCE: 350 CD/M² (TYP.)
8. BACKLIGHT TYPE: WHITE LED, I_f=100mA, V_f=2.9V~3.1V
9. TOP POLARIZER SURFACE TREATMENT: TBD
10. ONLY THE SINGLE LAYER AREA ON FPC IS BENDABLE AND THE MINIMUM BEND RADIUS IS 1.5MM
11. UNMARKED TOLERANCE: ±0.2MM
12. ROHS COMPLIANT

MULTI-INNO TECHNOLOGY CO., LTD.	
DRAWN BY: TUFFY	MODULE P/N: MI0266AT-1
CHECKED BY:	SCALE : 1/1
APPROVED BY:	UNIT: mm
VERSION NO: 01	SHEET NO: 1/1
VER. REVISED DESCRIPTION	DESCRIPTION: TFT MODULE

01	FIRST ISSUE	TUFFY	2025.11.04
VER.	REVISED DESCRIPTION	REVISER	DATE