



PIN ASSIGNMENT	
PIN	SYMBOL
1	SCLK
2	SI
3	SCS
4	EXTCOMIN
5	DISP
6	VDDA
7	VDD
8	EXTMODE
9	VSS
10	VSSA

NOTES:

1. DISPLAY TYPE: TFT, REFLECTIVE WITH SLIGHT TRANSMISSIVE, NORMALLY WHITE.
2. OPERATING VOLTAGE: VDD=VDDA=5.0V.
3. VIEWING DIRECTION: FULL VIEWING ANGLE $\triangle 3$
4. IC DRIVER: DATA STORAGE WITHIN PANEL.
5. OPERATING TEMP.: -20°C ~ 70°C.
6. STORAGE TEMP.: -30°C ~ 80°C.
7. LED BACKLIGHT: -.
8. SURFACE LUMINANCE: TBD.
9. TREATMENT OF TOP SURFACE: GLARE. $\triangle 2$
10. GENERAL TOLERANCE: ±0.2mm.
11. RoHS COMPLIANT.

MIT MULTI-INNO TECHNOLOGY CO., LTD.

DRAWN BY:	RITA	2019.05.27		MODULE P/N:
CHECKED BY:				MI0270DT-1
APPROVED BY:			SCALE : 1/1	DESCRIPTION:
VERSION NO:	03		UNIT: mm	TFT MODULE
			SHEET NO.: 1/1	

VER.	REVISED DESCRIPTION	REVISER	DATE
03	CORRECT THE VIEWING DIRECTION.	RITA	2020.01.16
02	CORRECT THE TREATMENT OF TOP SURFACE.	RITA	2019.10.16
01	FIRST ISSUE	RITA	2019.05.27