



TFT PIN DESCRIPTION	
PIN	SYMBOL
1	GND
2	LEDA
3	LEDA
4	LEDK
5	LEDK
6	GND
7	VDD(-5V)
8	VDD(-5V)
9	GND
10	VDD(+5V)
11	VDD(+5V)
12	GND
13	IOVCC(1.8V)
14	IOVCC(1.8V)
15	GND
16	RESET
17	GND
18	TE
19	GND
20	NC
21	NC
22	NC
23	GND
24	LAN2_P
25	NC
26	LAN2_N
27	GND
28	CLK_P
29	NC
30	CLK_N
31	GND
32	LAN1_P
33	NC
34	LAN1_N
35	GND
36	LANO_P
37	NC
38	LANO_N
39	GND

- NOTES:
1. DISPLAY TYPE: A-SI SFT.
  2. OPERATING VOLTAGE: VDD=±5.0V, IOVDD=1.8V.
  3. VIEWING DIRECTION: FULL VIEWING ANGLE.
  4. DRIVER IC: ILI9881C.
  5. OPERATING TEMP.: -20°C ~ 70°C.
  6. STORAGE TEMP.: -30°C ~ 80°C.
  7. LED BACKLIGHT: 8-CHIP WHITE LED, If=40mA, Vf=12.8V(TYP.).
  8. TOP POLARIZER SURFACE TREATMENT: HC.
  9. SURFACE LUMINANCE: 380CD/M<sup>2</sup>(TYP).
  10. MATED CONNECTOR: FH26W-39S-0.3SHW.
  11. GENERAL TOLERANCE: ±0.2MM.
  12. ROHS COMPLIANT.

DETAIL:A  
SCALE 4:1

MULTI-INNO TECHNOLOGY CO.,LTD.			
DRAWN BY:	CAROL	2019.07.17	MODULE P/N:
CHECKED BY:			MI0340AT-1
APPROVED BY:			DESCRIPTION:
VERSION NO:	01		TFT MODULE
			SCALE : 1/1
			UNIT: mm
			SHEET NO.: 1/1

VER.	REVISED DESCRIPTION	REVISER	DATE
01	FIRST ISSUE	CAROL	2019.07.17