



弯折示意图
FPC展开出货



DETAIL A
(SCALE 100:1)



NOTES:

1. DISPLAY TYPE: TFT, TRANSMISSIVE, NORMALLY BLACK
2. OPERATING VOLTAGE: VCC=2.8V (TYP.)
3. VIEWING DIRECTION: WIDE VIEWING ANGLE
4. DRIVER IC: HX8363A
5. OPERATING TEMP.: -20°C ~ 70°C
6. STORAGE TEMP.: -30°C ~ 80°C
7. LED BACKLIGHT: 6-CHIP WHITE LED, IF=20mA, VF=18V~21V
8. SURFACE LUMINANCE: 120CD/M² (TYP.)
9. TOP POLARIZER SURFACE TREATMENT: TBD
10. RECOMMEND MATCHING CONNECTOR: 51404-4090 OR EQUIVALENT
11. THE SINGLE LAYER AREA OF FPC IS BENDABLE AND THE BENDING RADIUS MUST BE NOT LESS THAN 1.5MM
12. GENERAL TOLERANCE: ±0.2MM
13. ROHS COMPLIANT

PIN DESCRIPTION	
PIN	SYMBOL
1	DE
2	GND
3	GND
4	GND
5	NC
6	RO
7	R1
8	R2
9	R3
10	R4
11	R5
12	G0
13	G1
14	G2
15	G3
16	G4
17	G5
18	B0
19	B1
20	B2
21	B3
22	B4
23	B5
24	SCL
25	SDA
26	/CS
27	DOTCLK
28	/RESET
29	HSYNC
30	VSYNC
31	VCC
32	VCC
33	GND
34	LED_A
35	LED_K
36	GND
37	NC(XR)
38	NC(YD)
39	NC(XL)
40	NC(YU)

MIR MULTI-INNO TECHNOLOGY CO., LTD.

DRAWN BY:	CAROL	2014.06.24		MODULE P/N:
CHECKED BY:			SCALE :	1/1
APPROVED BY:			UNIT:	mm
VERSION NO:	02		SHEET NO.:	1/1
				DESCRIPTION:
				TFT MODULE

02	ADD RTP SOLDERING PAD IN FPC	CAROL	2015.01.28
01	FIRST ISSUE	CAROL	2014.06.24
VER.	REVISED DESCRIPTION	REVISOR	DATE