


PIN ASSIGNMENT			
1	LEDK	28	R0
2	LEDK	29	R1
3	LEDA	30	R2
4	LEDA	31	R3
5	NC	32	R4
6	NC	33	R5
7	NC	34	R6
8	RESET	35	R7
9	SPENA	36	HSYNC
10	SPCLK	37	VSYNC
11	SPDAT	38	DCLK
12	B0	39	NC
13	B1	40	NC
14	B2	41	VDD
15	B3	42	VDD
16	B4	43	NC
17	B5	44	NC
18	B6	45	NC
19	B7	46	NC
20	G0	47	NC
21	G1	48	NC
22	G2	49	NC
23	G3	50	NC
24	G4	51	NC
25	G5	52	DEN
26	G6	53	GND
27	G7	54	GND



- NOTES:
1. DISPLAY TYPE: TFT/TRANSMISSIVE/NORMALLY BLACK
  2. VIEWING DIRECTION: FULL VIEWING ANGLE
  3. OPERATING VOLTAGE: VDD=3.3V
  4. DRIVER IC: ST7272A
  5. OPERATING TEMP.: -30°C ~ 85°C
  6. STORAGE TEMP.: -30°C ~ 85°C
  7. BACKLIGHT: 6-CHIP WHITE LED, IF=20mA, Vf=19.2V±1.2V
  8. SURFACE LUMINANCE: 550CD/M<sup>2</sup>(TYP.)
  9. TOP POLARIZER SURFACE TREATMENT: ANTI-GLARE
  10. GENERAL TOLERANCE: ±0.2mm
  11. ROHS COMPLIANT

VER.	REVISED DESCRIPTION	REVISER	DATE
03	CORRECT THE FPC, THERE ARE NO COMPONENTS ON THE FPC.	RITA	2020.09.27
02	CORRECT THE DESIGN OF IRON FRAME, ADDING IRON FRAME GROOVES.	RITA	2019.07.11
01	FIRST ISSUE	RITA	2018.05.30

**MULTI-INNO TECHNOLOGY CO., LTD.**

DRAWN BY:	RITA	20180530	SCALE : 1/1
CHECKED BY:			UNIT: mm
APPROVED BY:			
VERSION NO:	03		
MODULE P/N:			MI0350AUT-1
DESCRIPTION:			TFT MODULE