


PIN DESCRIPTION			
PIN	SYMBOL	PIN	SYMBOL
1	LEDK	28	R0
2	LEDK	29	R1
3	LEDA	30	R2
4	LEDA	31	R3
5	NC	32	R4
6	NC	33	R5
7	NC	34	R6
8	RESET	35	R7
9	SPENA	36	HSYNC
10	SPCLK	37	VSYNC
11	SPDAT	38	DCLK
12	B0	39	NC
13	B1	40	NC
14	B2	41	VDD
15	B3	42	VDD
16	B4	43	NC
17	B5	44	NC
18	B6	45	NC
19	B7	46	NC
20	G0	47	NC
21	G1	48	NC
22	G2	49	NC
23	G3	50	NC
24	G4	51	NC
25	G5	52	DEN
26	G6	53	GND
27	G7	54	GND



- NOTES:
1. DISPLAY TYPE: TFT, TRANSMISSIVE, NORMALLY BLACK
 2. OPERATING VOLTAGE: VDD=3.3V
 3. VIEWING DIRECTION: FULL VIEWING ANGLE
 4. DRIVER IC: ST7272A
 5. OPERATING TEMP.: -30°C ~ 85°C
 6. STORAGE TEMP.: -30°C ~ 85°C
 7. LED BACKLIGHT: 6-CHIP WHITE DUAL-DICE LEDES, If=40mA, Vf=19.2V
 8. TOP POLARIZER SURFACE TREATMENT: ANTI-GLARE
 9. SURFACE LUMINANCE: 1000CD/M² (TYP)
 10. THE SINGLE LAYER AREA OF FPC IS BENDABLE AND THE BENDING RADIUS MUST BE NOT LESS THAN 1.5MM
 11. GENERAL TOLERANCE: ±0.2MM
 12. ROHS COMPLIANT

Mit MULTI-INNO TECHNOLOGY CO., LTD.

DRAWN BY:	CAROL	2021.05.07		MODULE P/N:
CHECKED BY:			SCALE : 1/1	MI0350AUT-4
APPROVED BY:			UNIT: mm	DESCRIPTION:
VERSION NO.:	01		SHEET NO.: 1/1	TFT MODULE

01	FIRST ISSUE	CAROL	2021.05.07
VER.	REVISED DESCRIPTION	REVISER	DATE