





DETAIL A
(SCALE 2:1)



BACKLIGHT CIRCUIT DIAGRAM

NOTES:

1. DISPLAY TYPE: TFT, TRANSMISSIVE, NORMALLY WHITE
2. OPERATING VOLTAGE: VCC=3.0V (TYP.)
3. VIEWING DIRECTION: 6 O'CLOCK
4. DRIVER IC: ILI9341V
5. OPERATING TEMP.: -20°C ~ 70°C
6. STORAGE TEMP.: -30°C ~ 80°C
7. LED BACKLIGHT: WHITE LED, IF=20mA, VF=19.2V±1.2V
8. SURFACE LUMINANCE: 190 CD/M² (TYP.)
9. TOP POLARIZER SURFACE TREATMENT: GLARE
10. GENERAL TOLERANCE: ±0.2MM
11. ROHS COMPLIANT

PIN DESCRIPTION	
PIN	SYMBOL
1	VL1
2	GND
3	VL2
4	GND
5	VSHD
6	GND
7	GND
8	GND
9	VSYNC
10	GND
11	RESET
12	GND
13	GND
14	GND
15	CS
16	GND
17	SDO
18	SDI
19	GND
20	SCL
21	GND
22	B5
23	B4
24	B3
25	B2
26	B1
27	B0
28	ENAB
29	GND
30	HSYNC
31	GND
32	DCLK
33	GND
34	G5
35	G4
36	G3
37	G2
38	G1
39	G0
40	GND
41	R5
42	R4
43	R3
44	R2
45	R1
46	R0
47	GND
48	GND
49	GND
50	GND



MULTI-INNO TECHNOLOGY CO., LTD.

DRAWN BY:	CAROL	2019.02.25		MODULE P/N:
CHECKED BY:			SCALE : 1/1	MI0350B4T-6
APPROVED BY:			UNIT: mm	DESCRIPTION:
VERSION NO:	01		SHEET NO.: 1/1	TFT MODULE

01	FIRST ISSUE	CAROL	2019.02.25
VER.	REVISED DESCRIPTION	REVISOR	DATE