


TFT PIN DESCRIPTION			
PIN	SYMBOL	PIN	SYMBOL
1	LEDK	28	D16
2	LEDK	29	D17
3	LEDA	30	D18
4	LEDA	31	D19
5	NC	32	D20
6	NC	33	D21
7	NC	34	D22
8	RESET	35	D23
9	SPENA	36	HSYNC
10	SPCK	37	VSYNC
11	SPDA	38	CLK
12	D00	39	NC
13	D01	40	NC
14	D02	41	VDD
15	D03	42	VDD
16	D04	43	NC
17	D05	44	NC
18	D06	45	NC
19	D07	46	NC
20	D08	47	NC
21	D09	48	NC
22	D10	49	NC
23	D11	50	NC
24	D12	51	NC
25	D13	52	DEN
26	D14	53	GND
27	D15	54	GND



BACKLIGHT CIRCUIT DIAGRAM

- NOTES:
1. DISPLAY TYPE: TFT, TRANSMISSIVE, NORMALLY WHITE
 2. VIEWING DIRECTION: 12 O'CLOCK
 3. OPERATING VOLTAGE: VDD=3.3V
 4. DRIVER IC: NV3035C
 5. OPERATING TEMP.: -20°C ~ 70°C
 6. STORAGE TEMP.: -30°C ~ 80°C
 7. BACKLIGHT: 12-CHIP WHITE LED, IF=40mA, VF=19.2V
 8. SURFACE LUMINANCE: 1000cd/m²(TYP)
 9. TOP POLARIZER SURFACE TREATMENT: ANTI-GLARE
 10. GENERAL TOLERANCE: ±0.2mm
 11. ROHS COMPLIANT

Mit MULTI-INNO TECHNOLOGY CO., LTD.

DRAWN BY:	CAROL	2019.06.21		MODULE P/N:
CHECKED BY:			SCALE : 1/1	M0350C4T-8
APPROVED BY:			UNIT: mm	DESCRIPTION:
VERSION NO:	01		SHEET NO.: 1/1	TFT MODULE

VER.	REVISED DESCRIPTION	REVISER	DATE
01	FIRST ISSUE	CAROL	2019.06.21