


PIN DESCRIPTION	
PIN	SYMBOL
1	NC
2	GND
3	NC
4	NC
5	NC
6	NC
7	NC
8	NC
9	NC
10	NC
11	NC
12	NC
13	NC
14	NC
15	NC
16	NC
17	NC
18	NC
19	NC
20	NC
21	NC
22	NC
23	NC
24	NC
25	NC
26	NC
27	NC
28	VDDA
29	VDDI
30	GND
31	CS
32	AO
33	RST
34	SCL
35	SDA
36	NC
37	NC
38	GND
39	NC
40	NC

NOTES:

1. DISPLAY TYPE: B/W/R TFT, REFLECTIVE, NORMALLY WHITE
2. OPERATING VOLTAGE: VDDI=2.8V (TYP.)
3. VIEWING DIRECTION: FULL VIEWING ANGLE
4. DRIVER IC: ST7306
5. OPERATING TEMP.: -20°C ~ 70°C
6. STORAGE TEMP.: -30°C ~ 80°C
7. TOP POLARIZER SURFACE TREATMENT: TBD
8. ONLY THE SINGLE LAYER AREA ON FPC IS BENDABLE AND THE MINIMUM BEND RADIUS IS 1.5MM
9. GENERAL TOLERANCE: ±0.3MM
10. ROHS COMPLIANT

 MULTI-INNO TECHNOLOGY CO., LTD.			
DRAWN BY:	CAROL	2022.06.08	MODULE P/N:
CHECKED BY:			MI0420FT-1
APPROVED BY:			DESCRIPTION:
VER. REVISED DESCRIPTION	REVISER	DATE	TFT MODULE

01	FIRST ISSUE	CAROL	2022.06.08
VER.	REVISED DESCRIPTION	REVISER	DATE

SCALE : 1/1	UNIT: mm	SHEET NO.: 1/1
-------------	----------	----------------