


DETAIL A
(SCALE 4:1)



LED CIRCUIT DIAGRAM

PIN ASSIGNMENT FOR LCD	
NO.	SYMBOL
1	LEDK
2	LEDA
3	GND
4	VDD
5	RO
6	R1
7	R2
8	R3
9	R4
10	R5
11	R6
12	R7
13	G0
14	G1
15	G2
16	G3
17	G4
18	G5
19	G6
20	G7
21	B0
22	B1
23	B2
24	B3
25	B4
26	B5
27	B6
28	B7
29	GND
30	DCLK
31	DISP
32	HSYNC
33	VSYNC
34	DE
35	NC
36	GND
37	NC(XR)
38	NC(YD)
39	NC(XL)
40	NC(YU)

NOTES:

1. DISPLAY TYPE: TFT, TRANSMISSIVE, NORMALLY BLACK
2. OPERATING VOLTAGE: VDD=3.3V
3. VIEWING DIRECTION: FULL VIEWING ANGLE
4. DRIVER IC: SC7283
5. OPERATING TEMP.: -30°C ~ 85°C
6. STORAGE TEMP.: -30°C ~ 85°C
7. LED BACKLIGHT: 10-CHIP WHITE LED, If=40mA, Vf=14.0~17.0V
8. SURFACE LUMINANCE: 1000CD/M²(TYP.)
9. TOP POLARIZER SURFACE TREATMENT: ANTI-GLARE
10. GENERAL TOLERANCE: ±0.3MM
11. ROHS COMPLIANT

01	FIRST ISSUE	CAROL	2019.01.25
VER.	REVISED DESCRIPTION	REVISER	DATE

MULTI-INNO TECHNOLOGY CO., LTD.		DRAWN BY:	CAROL 2019.01.25	SCALE : 1/1	MODULE P/N:
		CHECKED BY:		UNIT:	mm
APPROVED BY:		VERSION NO:	01	DESCRIPTION:	
				TFT MODULE	