


PIN DESCRIPTION	
PIN	SYMBOL
1	VLED+
2	VLED-
3	GND
4	GND
5	VDD
6	VDDIO
7	VSYNC
8	HSYNC
9	DE
10	PCLK
11	RESET
12	CS
13	SCL
14	SDI
15	SDO
16	DB0(B0)
17	DB1
18	DB2
19	DB3
20	DB4
21	DB5
22	DB6
23	DB7(B7)
24	GND
25	DB8(G0)
26	DB9
27	DB10
28	DB11
29	DB12
30	DB13
31	DB14
32	DB15(G7)
33	GND
34	DB16(R0)
35	DB17
36	DB18
37	DB19
38	DB20
39	DB21
40	DB22
41	DB23(R7)
42	GND

NOTES:

1. DISPLAY TYPE: TFT, TRANSMISSIVE, NORMALLY BLACK
2. OPERATING VOLTAGE: VDD=3.3V (TYP.)
3. VIEWING DIRECTION: FULL VIEWING ANGLE
4. DRIVER IC: ILI9806E
5. OPERATING TEMP.: -20°C ~ 70°C
6. STORAGE TEMP.: -30°C ~ 80°C
7. LED BACKLIGHT: 8-CHIP WHITE DUAL-DICE LEDS, IF=40mA, VF=22.4V~27.2V
8. SURFACE LUMINANCE: 800CD/M² (TYP.)
9. TOP POLARIZER SURFACE TREATMENT: GLARE
10. ONLY THE SINGLE LAYER AREA ON FPC IS BENDABLE AND THE MINIMUM BEND RADIUS IS 1.5MM
11. GENERAL TOLERANCE: ±0.3MM
12. ROHS COMPLIANT

 MULTI-INNO TECHNOLOGY CO., LTD.

01	FIRST ISSUE	CAROL	2022.09.07		MODULE P/N:
VER.	REVISED DESCRIPTION	REVISER	DATE	APPROVED BY:	MI0430Z1T-10
				VERSION NO: 01	DESCRIPTION:
					TFT MODULE