



PIN ASSIGNMENT	
1	LED_K
2	LED_A
3	NC(GND)
4	VDD
5	R0
6	R1
7	R2
8	R3
9	R4
10	R5
11	R6
12	R7
13	G0
14	G1
15	G2
16	G3
17	G4
18	G5
19	G6
20	G7
21	B0
22	B1
23	B2
24	B3
25	B4
26	B5
27	B6
28	B7
29	GND
30	CLK
31	DISP
32	HSYNC
33	VSYNC
34	DE
35	NC
36	GND
37	XR
38	YD
39	XL
40	YU

- NOTES:
1. DISPLAY TYPE: TFT / TRANSMISSIVE / NORMALLY BLACK.
 2. VIEWING DIRECTION: FULL VIEWING ANGLE.
 3. OPERATING VOLTAGE: VDD=3.3V.
 4. DRIVER IC: ST7262.
 5. OPERATING TEMP.: -20°C ~ 70°C.
 6. STORAGE TEMP.: -30°C ~ 80°C.
 7. BACKLIGHT: 18-CHIP WHITE LED, IF=60mA, Vf=19.2±1.2V.
 8. SURFACE LUMINANCE: 480CD/M² (TYP.).
 9. TOP POLARIZER SURFACE TREATMENT: ANTI-GLARE.
 10. GENERAL TOLERANCE: ±0.3mm.
 11. ROHS COMPLIANT.

MIL MULTI-INNO TECHNOLOGY CO.,LTD.

DRAWN BY:	RITA	20190823	SCALE : 1/1	MODULE P/N:
CHECKED BY:			UNIT:	MI0500AHT-3RP
APPROVED BY:			mm	DESCRIPTION:
VERSION NO:	02			TFT + RTP MODULE

VER.	REVISED DESCRIPTION	REVISER	DATE
02	MODIFY PIN3 FROM NC TO NC(GND).	CAROL	2019.10.24
01	FIRST ISSUE	RITA	2019.08.23