



PIN ASSIGNMENT	
PIN NO.	SYMBOL
1	NC
2	VDD
3	VDD
4	NC(VDDI)
5	RESET
6	STBYB
7	GND
8	RXIN0-
9	RXIN0+
10	GND
11	RXIN1-
12	RXIN1+
13	GND
14	RXIN2-
15	RXIN2+
16	GND
17	RXCLK-
18	RXCLK+
19	GND
20	RXIN3-
21	RXIN3+
22	GND
23	NC
24	NC
25	GND
26	NC
27	NC
28	SELB
29	NC
30	GND
31	LED_K
32	LED_K
33	L/R
34	U/D
35	NC
36	NC
37	NC
38	NC
39	LED_A
40	LED_A

- NOTES:
1. DISPLAY TYPE: TFT / TRANSMISSIVE / NORMALLY BLACK.
  2. VIEWING DIRECTION: FULL VIEWING ANGLE.
  3. OPERATING VOLTAGE: VDD=3.3V.
  4. DRIVER IC: ST7262-G4-1-H.
  5. OPERATING TEMP.: -30°C ~ 85°C.
  6. STORAGE TEMP.: -30°C ~ 85°C.
  7. BACKLIGHT: 18-CHIP WHITE LED, IF=60mA, Vf=19.2±1.2V.
  8. SURFACE LUMINANCE: 600CD/M<sup>2</sup> (TYP.).
  9. TOP POLARIZER SURFACE TREATMENT: ANTI-GLARE.
  10. RECOMMEND MATCHING CONNECTOR: FH28-40S-0.5SH OR EQUIVALENT.
  11. THE SINGLE LAYER AREA OF FPC IS BENDABLE AND THE BENDING RADIUS MUST BE NOT LESS THAN 1.5MM.
  12. GENERAL TOLERANCE: ±0.3mm.
  13. ROHS COMPLIANT.

**Mit** MULTI-INNO TECHNOLOGY CO.,LTD.

DRAWN BY:	RITA	2020.07.08		MODULE P/N:
CHECKED BY:			SCALE : 1/1	MI0500AKT-1
APPROVED BY:			UNIT: mm	DESCRIPTION:
VERSION NO:	01		SHEET NO.: 1/1	TFT MODULE

01	FIRST ISSUE	RITA	2020.07.08
VER.	REVISED DESCRIPTION	REVISER	DATE