


DETAIL A
(SCALE 100:1)



LED CIRCUIT DIAGRAM

PIN ASSIGNMENT	
PIN NO	SYMBOL
1	GND
2	RSE
3	VCC
4	GND
5	VDD 2.8V
6	VDD 2.8V
7	GND
8	GND
9	D0P
10	D0N
11	GND
12	D1P
13	D1N
14	GND
15	CLKP
16	CLKN
17	GND
18	D2P
19	D2N
20	GND
21	D3P
22	D3N
23	GND
24	GND
25	LEDA
26	LEDA
27	LEDA
28	LEDK
29	LEDK
30	LEDK

NOTES:

1. DISPLAY TYPE: TFT, TRANSMISSIVE, NORMALLY BLACK Δ
2. OPERATING VOLTAGE: VDD=2.8V
3. VIEWING DIRECTION: FULL VIEWING ANGLE Δ
4. DRIVER IC: ILI9881D
5. OPERATING TEMP.: -20°C ~ 70°C
6. STORAGE TEMP.: -30°C ~ 80°C
7. LED BACKLIGHT: 15-CHIP WHITE LED, If=100mA, Vf=8.1V~10.5V
8. TOP POLARIZER SURFACE TREATMENT: ANTI-GLARE
9. SURFACE LUMINANCE: 320CD/M²(TYP.)
10. GENERAL TOLERANCE: ±0.3MM
11. ROHS COMPLIANT

MULTI-INNO TECHNOLOGY CO., LTD.

DRAWN BY:	RITA	2019.07.12		MODULE P/N:
CHECKED BY:			SCALE : 1/1	MI0550CT-1
APPROVED BY:			UNIT: mm	DESCRIPTION:
VERSION NO:	02		SHEET NO.: 1/1	TFT MODULE

VER.	REVISED DESCRIPTION	REVISER	DATE
02	CORRECT THE THE DISPLAY TYPE AND VIEWING DIRECTION	RITA	2019.08.16
01	FIRST ISSUE	RITA	2019.07.12