



NOTES:

1. DISPLAY TYPE: TFT, TRANSMISSIVE, NORMALLY WHITE
2. OPERATING VOLTAGE: VCC=5.0V (TYP.)
3. VIEWING DIRECTION: 12 O'CLOCK
4. DRIVER IC: -
5. OPERATING TEMP.: -10°C ~ 60°C
6. STORAGE TEMP.: -20°C ~ 70°C
7. LED BACKLIGHT: 14-CHIP WHITE LED, IF=140mA, VF=6.4V
8. SURFACE LUMINANCE: 180CD/M² (TYP.)
9. TOP POLARIZER SURFACE TREATMENT: ANTI-GLARE
10. RECOMMEND MATCHING CONNECTOR: BHSR-02VS-1 OR EQUIVALENT
11. CABLE IS "KURABE 3633 AWG28"
12. GENERAL TOLERANCE: ±0.3MM
13. ROHS COMPLIANT

PIN	DESCRIPTION	SYMBOL
1	GND	
2	VCC	
3	VGL	
4	VGH	
5	STVD	
6	STVU	
7	CKV	
8	U/D	
9	OEV	
10	VCOM	
11	VCOM	
12	L/R	
13	MOD	
14	OEHL	
15	STHL	
16	STHR	
17	CPH3	
18	CPH2	
19	CPH1	
20	VCC	
21	GND	
22	VR	
23	VG	
24	VB	
25	AVDD	
26	AVSS	

PIN	DESCRIPTION FOR RTP	SYMBOL
1	X-	
2	Y-	
3	X+	
4	Y+	

MULTI-INNO TECHNOLOGY CO., LTD.			
DRAWN BY:	CAROL 2012.05.15		MODULE P/N:
CHECKED BY:		SCALE : 1/1	MI0560DT-2
APPROVED BY:		UNIT: mm	DESCRIPTION:
VERSION NO:	01	SHEET NO.: 1/1	TFT + RTP MODULE

01	FIRST ISSUE	CAROL	2012.05.15
VER.	REVISED DESCRIPTION	REVISER	DATE