


DETAIL A
SCALE 3:1

NOTE:

1. DISPLAY TYPE: TFT, TRANSMISSIVE, NORMALLY WHITE
2. OPERATING VOLTAGE: VCC=3.3V (TYP.)
3. VIEWING DIRECTION: 12 O'CLOCK
4. DRIVER IC: -
5. OPERATING TEMP.: -20°C ~ 70°C
6. STORAGE TEMP.: -30°C ~ 80°C
7. LED BACKLIGHT: WHITE LED
BUILT-IN BACKLIGHT DRIVE: VLED=5.0V
8. SURFACE LUMINANCE: 350CD/M² (TYP.)
9. TOP POLARIZER SURFACE TREATMENT: ANTI-GLARE
10. THE RECOMMENDED FPC CONNECTOR IS FH19SC-40S-0.5SH
11. THE BENDING RADIUS OF FPC SHOULD BE LARGER THAN 1.0MM
12. GENERAL TOLERANCE: ±0.3MM
13. ROHS COMPLIANT

PIN DESCRIPTION	
PIN	SYMBOL
1	VLED
2	VLED
3	ADJ
4	GLED
5	GLED
6	VCC
7	VCC
8	MODE
9	DE
10	VS
11	HS
12	GND
13	B5
14	B4
15	B3
16	GND
17	B2
18	B1
19	B0
20	GND
21	G5
22	G4
23	G3
24	GND
25	G2
26	G1
27	G0
28	GND
29	R5
30	R4
31	R3
32	GND
33	R2
34	R1
35	R0
36	GND
37	DCLK
38	GND
39	L/R
40	U/D

 MULTI-INNO TECHNOLOGY CO., LTD.

DRAWN BY:	RITA	2021.03.05		MODULE P/N:
CHECKED BY:			SCALE : 1/1	MI0560GT-1
APPROVED BY:			UNIT: mm	DESCRIPTION:
VERSION NO:	01		SHEET NO.: 1/1	TFT MODULE

OX	FIRST ISSUE	RITA	2021.03.05
VER.	REVISED DESCRIPTION	REVISOR	DATE