



PIN ASSIGNMENT	
NO.	SYMBOL
1	VSS
2	DCLK
3	HS
4	VS
5	VSS
6	R0
7	R1
8	R2
9	R3
10	R4
11	R5
12	VSS
13	G0
14	G1
15	G2
16	G3
17	G4
18	G5
19	VSS
20	B0
21	B1
22	B2
23	B3
24	B4
25	B5
26	VSS
27	DEN
28	VCC
29	VCC
30	R/L
31	U/D
32	NC
33	VSS

NOTES:

1. DISPLAY TYPE: TFT, TRANSMISSIVE, NORMALLY WHITE.
2. OPERATING VOLTAGE: VCC=3.3V.
3. VIEWING DIRECTION: 12 O'CLOCK.
4. DRIVER IC: TBD.
5. OPERATING TEMP.: -30°C ~ 85°C.
6. STORAGE TEMP.: -30°C ~ 85°C.
7. LED BACKLIGHT: 30-CHIP WHITE LED, If=200mA, Vf=9.6±0.6V.
8. TOP POLARIZER SURFACE TREATMENT: TBD.
9. SURFACE LUMINANCE: 1200CD/M²(TYP.).
10. GENERAL TOLERANCE: ±0.3MM.
11. ROHS COMPLIANT.



MULTI-INNO TECHNOLOGY CO., LTD.

DRAWN BY:	RITA	2019.10.16	SCALE : 1/1	MODULE P/N:
CHECKED BY:			UNIT:	MI0570ADT-1
APPROVED BY:			mm	DESCRIPTION:
VERSION NO:	01			TFT MODULE

01	FIRST ISSUE	RITA	2019.10.16
VER.	REVISED DESCRIPTION	REVISER	DATE