



DETAIL A  
(SCALE 40:1)

PIN ASSIGNMENT	
PIN	SYMBOL
1	VCC
2	VCC
3	VSS
4	VSS
5	INO-
6	INO+
7	VSS
8	IN1-
9	IN1+
10	VSS
11	IN2-
12	IN2+
13	VSS
14	CLK-
15	CLK+
16	VSS
17	BL_ADJ
18	VBL
19	VSS
20	VSS

NOTES:

1. DISPLAY TYPE: TFT, TRANSMISSIVE, NORMALLY WHITE
2. OPERATING VOLTAGE: VCC=3.3V (TYP.)
3. VIEWING DIRECTION: 12:00 O'CLOCK
4. DRIVER IC: EK79713B + EK73202A
5. OPERATING TEMP.: -20°C ~ 70°C
6. STORAGE TEMP.: -30°C ~ 80°C
7. BACKLIGHT: 24-CHIP WHITE LED  
BUILT-IN BACKLIGHT DRIVER: VBL=5.0V
8. SURFACE LUMINANCE: 550CD/M<sup>2</sup> (TYP.)
9. TOP POLARIZER SURFACE TREATMENT: ANTI-GLARE
10. CN1 PADS RESERVD FOR RGB INTERFACE  
CN2 FOR LVDS INTERFACE
11. THE SINGLE LAYER AREA OF FPC IS BENDABLE AND THE  
BENDING RADIUS MUST BE NOT LESS THAN 1.5MM
12. GENERAL TOLERANCE: ±0.3MM
13. ROHS COMPLIANT

MULTI-INNO TECHNOLOGY CO., LTD.			
DRAWN BY:	RITA	2022.02.28	MODULE P/N:
CHECKED BY:			MI0700A2T-30
APPROVED BY:			SCALE : 1/1
VERSION NO:	01		UNIT: mm
			SHEET NO.: 1/1
			DESCRIPTION:
			TFT MODULE

01	FIRST ISSUE	RITA	2022.02.28
VER.	REVISED DESCRIPTION	REVISER	DATE