



- NOTES FOR TFT:
1. DISPLAY TYPE: TFT, TRANSMISSIVE, NORMALLY WHITE
  2. OPERATING VOLTAGE: VCC=3.3V (TYP.)
  3. VIEWING DIRECTION: 12 O'CLOCK
  4. DRIVER IC: HX8262 + HX8678
  5. LED BACKLIGHT: 30-CHIP WHITE LED, IF=225ma, VF=9.2V
  6. LED P/N: 01.JT.CB320ZB-B
  7. TOP POLARIZER SURFACE TREATMENT: ANTI-GLARE
  8. BEZEL MATERIAL: STAINLESS STEEL

- NOTES FOR CTP:
1. 7.0 INCH PROJECTIVE CAPACITIVE TOUCH PANEL
  2. COVER GLASS + SENSOR GLASS + FPCA
  3. OPERATING VOLTAGE: VDD=3.3V
  4. DRIVER IC: FT5426 (SMT)
  5. RESOLUTION: 800\*480
  6. MULTI FINGER: UP TO 5
  7. HARDNESS OF COVER SURFACE: 7H

- NOTES FOR OTHERS:
1. OPERATING TEMP.: -20°C ~ 70°C
  2. STORAGE TEMP.: -30°C ~ 80°C
  3. SURFACE LUMINANCE: 850 CD/M<sup>2</sup> (TYP.)
  4. GENERAL TOLERANCE: ±0.3MM
  5. ROHS COMPLIANT

PIN DESCRIPTION FOR CN2	
PIN	SYMBOL
1	VCC
2	VCC
3	VSS
4	VSS
5	INO-
6	INO+
7	VSS
8	INT-
9	INT+
10	VSS
11	IN2-
12	IN2+
13	VSS
14	CLK-
15	CLK+
16	VSS
17	NC
18	NC
19	VSS
20	VSS

PIN DESCRIPTION FOR CTP	
PIN	SYMBOL
1	VSS
2	VDD
3	SCL(SSEL)
4	NC(SCK)
5	SDA(MOSI)
6	NC(MISO)
7	RST
8	NC
9	INT
10	VSS

		MULTI-INNO TECHNOLOGY CO., LTD.	
DRAWN BY:	RITA 2016.05.03		MODULE P/N:
CHECKED BY:		SCALE : 1/1	M10700AJT-32CP
APPROVED BY:		UNIT: mm	DESCRIPTION:
VERSION NO:	01	SHEET NO.: 1/1	TFT + CTP MODULE

01	FIRST ISSUE	RITA	2016.05.03
VER.	REVISED DESCRIPTION	REVISER	DATE