



PIN DESCRIPTION	
PIN	SYMBOL
1	NC
2	DVDD
3	DVDD
4	NC
5	RESET
6	STBYB
7	GND
8	NIND0
9	PIND0
10	GND
11	NIND1
12	PIND1
13	GND
14	NIND2
15	PIND2
16	GND
17	NINC
18	PINC
19	GND
20	NIND3
21	PIND3
22	GND
23	NC
24	NC
25	GND
26	NC
27	NC
28	SELB
29	NC
30	GND
31	NC
32	NC
33	SHLR
34	UPDN
35	NC(K)
36	NC(A)
37	NC
38	NC
39	NC
40	NC

NOTES:

1. DISPLAY TYPE: TFT, TRANSMISSIVE, NORMALLY BLACK
2. OPERATING VOLTAGE: DVDD=3.3V (TYP.)
3. VIEWING DIRECTION: FULL VIEWING ANGLE
4. DRIVER IC: HX8249-A02+HX8678-C01
5. OPERATING TEMP.: -30°C ~ 80°C
6. STORAGE TEMP.: -30°C ~ 80°C
7. LED BACKLIGHT: 30-CHIP WHITE LED, IF=300mA, VF=8.4V~10.4V
8. SURFACE LUMINANCE: 1000 CD/M² (TYP.)
9. TOP POLARIZER SURFACE TREATMENT: ANTI-GLARE
10. ONLY THE SINGLE LAYER AREA ON FPC IS BENDABLE AND THE MINIMUM BEND RADIUS IS 1.5MM
11. GENERAL TOLERANCE: ±0.3MM
12. ROHS COMPLIANT



BACKLIGHT CIRCUIT DIAGRAM

MULTI-INNO TECHNOLOGY CO., LTD.			
DRAWN BY:	CAROL	2022.09.21	MODULE P/N:
CHECKED BY:			MIO700CDT-1
APPROVED BY:			DESCRIPTION:
VERSION NO:	01		TFT MODULE
VER.	REVISED DESCRIPTION	REVISOR	DATE

01	FIRST ISSUE	CAROL	2022.09.21
VER.	REVISED DESCRIPTION	REVISOR	DATE