


PIN DESCRIPTION FOR CON1	
PIN	SYMBOL
1	GND
2	GND
3	ADJ
4	VLED
5	VLED
6	VLED
7	VCC
8	VCC
9	DE
10	GND
11	GND
12	GND
13	B5
14	B4
15	B3
16	GND
17	B2
18	B1
19	B0
20	GND
21	G5
22	G4
23	G3
24	GND
25	G2
26	G1
27	G0
28	GND
29	R5
30	R4
31	R3
32	GND
33	R2
34	R1
35	R0
36	GND
37	GND
38	DCLK
39	GND
40	GND


PIN DESCRIPTION FOR RTP	
PIN	SYMBOL
1	Y2
2	X2
3	Y1
4	X1

NOTE:

1. DISPLAY TYPE: TFT, TRANSMISSIVE, NORMALLY WHITE
2. OPERATING VOLTAGE: VCC=3.3V (TYP.)
3. VIEWING DIRECTION: 12 O'CLOCK
4. DRIVER IC: HX8264-DO3+HX8664-B0
5. OPERATING TEMP.: -20°C ~ 70°C
6. STORAGE TEMP.: -30°C ~ 80°C
7. LED BACKLIGHT: 27-CHIP WHITE LED
BUILT-IN BACKLIGHT DRIVE: VLED=5.0V
8. SURFACE LUMINANCE: 440CD/M² (TYP.)
9. TOP POLARIZER SURFACE TREATMENT: ANTI-GLARE
10. THE SINGLE LAYER AREA OF FPC IS BENDABLE AND THE BENDING RADIUS MUST BE NOT LESS THAN 1.5MM
11. GENERAL TOLERANCE: ±0.3MM
12. ROHS COMPLIANT



PIXEL DETAIL
SCALE 100:1



BACKLIGHT CIRCUIT DIAGRAM

MULTI-INNO TECHNOLOGY CO., LTD.			
DRAWN BY:	CAROL 2021.05.19		MODULE P/N:
CHECKED BY:		SCALE : 1/1	MI0700N4T-10RP
APPROVED BY:		UNIT: mm	DESCRIPTION:
VERSION NO:	02	SHEET NO.: 1/1	TFT + RTP MODULE

VER.	REVISED DESCRIPTION	REVISER	DATE
02	CORRECT THE POSITION OF THE COMPONENT AREA ON THE FPC.	CAROL	2021.06.03
01	FIRST ISSUE	CAROL	2021.05.19