



PIN NO	SYMBOL
1	VCC
2	VCC
3	VSS
4	INO-
5	INO+
6	VSS
7	IN1-
8	IN1+
9	VSS
10	IN2-
11	IN2+
12	VSS
13	CLK-
14	CLK+
15	VSS
16	IN3-
17	IN3+
18	VSS
19	BL_ADJ
20	VBL

NOTES:

1. DISPLAY TYPE: TFT/TRANSMISSIVE/NORMALLY WHITE
2. OPERATING VOLTAGE: VCC=3.3V
3. VIEWING DIRECTION: 12 O'CLOCK
4. DRIVER IC: HX8264-E00+HX8664-B00 or EK9713CA+EK73002ACBE
5. OPERATING TEMP.: -20°C ~ 70°C
6. STORAGE TEMP.: -30°C ~ 80°C
7. LED BACKLIGHT: 21-CHIP WHITE LED, IF=140mA, VF=9.6V±1.2V
8. SURFACE LUMINANCE: 420CD/M²(TYP.)
9. TREATMENT OF TOP SURFACE: ANTI-GLARE
10. GENERAL TOLERANCE: ±0.3mm
11. ROHS COMPLIANT

MIT MULTI-INNO TECHNOLOGY CO., LTD.

DRAWN BY:	RITA	2019.06.14		MODULE P/N:
CHECKED BY:			SCALE : 1/1	MI0700S6T-1-B
APPROVED BY:			UNIT: mm	DESCRIPTION:
VERSION:	REVISED DESCRIPTION	REVISER	DATE	VERSION NO: 02
				SHEET NO.: 1/1
				TFT + PCBA MODULE

02	MODIFY THE IC DRIVER OF TFT FROM H0264+H08664 TO H0264-E00+H08664-B00 or EK9713CA+EK73002ACBE	CAROL	2021.10.11
01	FIRST ISSUE	RITA	2019.06.14