



DETAIL A
(SCALE 30:1)



DETAIL B
(SCALE 3:1)




BACKLIGHT CTRCUIT DIAGRAM

PIN DESCRIPTION FOR TFT	
PIN	SYMBOL
1	VCOM
2	VDD
3	VDD
4	NC
5	RESET
6	STBYB
7	GND
8	RXIN0-
9	RXIN0+
10	GND
11	RXIN1-
12	RXIN1+
13	GND
14	RXIN2-
15	RXIN2+
16	GND
17	RXCLKIN-
18	RXCLKIN+
19	GND
20	RXIN3-
21	RXIN3+
22	GND
23	NC
24	NC
25	GND
26	NC
27	DIMO
28	SELB
29	AVDD
30	GND
31	LED-
32	LED-
33	L/R
34	U/D
35	VGL
36	CABCEN1
37	CABCEN0
38	VGH
39	LED+
40	LED+
PIN DESCRIPTION FOR RTP	
PIN	SYMBOL
1	Y2
2	X2
3	Y1
4	X1

- NOTES:
1. DISPLAY TYPE: TFT, TRANSMISSIVE, NORMALLY WHITE
 2. OPERATING VOLTAGE: VDD=3.3V (TYP.)
 3. VIEWING DIRECTION: 12 O'CLOCK
 4. DRIVER IC: NT51008CH-D + NT52002H-D
 5. OPERATING TEMP.: -20°C ~ 70°C
 6. STORAGE TEMP.: -30°C ~ 80°C
 7. LED BACKLIGHT: 28-CHIP WHITE LED, IF=160mA, VF=18.9V~23.8V
 8. SURFACE LUMINANCE: 960CD/M² (TYP.)
 9. TOP POLARIZER SURFACE TREATMENT: GLARE
 10. GENERAL TOLERANCE: ±0.3MM
 11. ROHS COMPLIANT

 MULTI-INNO TECHNOLOGY CO., LTD.

01	FIRST ISSUE	RITA	2020.12.16		MODULE P/N:
VER.	REVISED DESCRIPTION	REVISER	DATE	APPROVED BY:	DESCRIPTION:
				01	TFT + RTP MODULE
				SCALE : 1/1	MI0700XT-23RP
				UNIT: mm	
				SHEET NO.: 1/1	