



- NOTES:
1. DISPLAY TYPE: TFT, TRANSMISSIVE, NORMALLY BLACK.
  2. OPERATING VOLTAGE: VDD=3.3V.
  3. VIEWING DIRECTION: 12:00 O'CLOCK.
  4. DRIVER IC: HX8282+HX8677.
  5. OPERATING TEMP.: -25°C ~ 80°C.
  6. STORAGE TEMP.: -30°C ~ 80°C.
  7. LED BACKLIGHT: 27-CHIP WHITE LED, IF=180mA, VF=9.6V.
  8. TOP POLARIZER SURFACE TREATMENT: GLARE.
  9. SURFACE LUMINANCE: 500CD/M<sup>2</sup>(TYP).
  10. GENERAL TOLERANCE: ±0.2MM.
  11. ROHS COMPLIANT.

TFT PIN DESCRIPTION	
PIN	SYMBOL
1	VCOM
2	VDD
3	VDD
4	NC
5	RESET
6	STBYB
7	GND
8	RXIN0-
9	RXIN0+
10	GND
11	RXIN1-
12	RXIN1+
13	GND
14	RXIN2-
15	RXIN2+
16	GND
17	RXCLKIN-
18	RXCLKIN+
19	GND
20	RXIN3-
21	RXIN3+
22	GND
23	NC
24	NC
25	GND
26	NC
27	DIM0
28	SELB
29	AVDD
30	GND
31	LED-
32	LED-
33	L/R
34	U/D
35	VGL
36	CABCEN1
37	CABCEN0
38	VGH
39	LED+
40	LED+

**MIT** MULTI-INNO TECHNOLOGY CO., LTD.

DRAWN BY:	CAROL	2021.04.09		MODULE P/N:
CHECKED BY:				M10700XT-26
APPROVED BY:			UNIT: mm	DESCRIPTION:
VERSION NO:	02		SHEET NO.: 1/1	TFT MODULE

02	CORRECT THE DRIVER IC P/N.	RITA	2021.04.12
01	FIRST ISSUE	CAROL	2021.04.09
VER.	REVISED DESCRIPTION	REVISOR	DATE