


PIN DESCRIPTION	
PIN	SYMBOL
1	NC
2	GND
3	D3P
4	D3N
5	GND
6	D2P
7	D2N
8	GND
9	D1P
10	D1N
11	GND
12	D0P
13	D0N
14	GND
15	CLKP
16	CLKN
17	GND
18	NC
19	NC
20	NC
21	NC
22	GND
23	RESX
24	NC
25	VCI
26	IOVCC
27	NC
28	GND
29	NC
30	NC

NOTES:

1. DISPLAY TYPE: TFT, REFLECTIVE, NORMALLY WHITE
2. OPERATING VOLTAGE: VCI=3.3V (TYP.)
3. VIEWING DIRECTION: FULL VIEWING ANGLE
4. DRIVER IC: IL9881C
5. OPERATING TEMP.: -20°C ~ 70°C
6. STORAGE TEMP.: -30°C ~ 80°C
7. TOP POLARIZER SURFACE TREATMENT: TBD
8. ONLY THE SINGLE LAYER AREA ON FPC IS BENDABLE AND THE MINIMUM BEND RADIUS IS 1.5MM
9. GENERAL TOLERANCE: ±0.4MM
10. ROHS COMPLIANT

 MULTI-INNO TECHNOLOGY CO., LTD.			
DRAWN BY:	RITA	20230324	MODULE P/N:
CHECKED BY:			MIO780AT-1
APPROVED BY:			DESCRIPTION:
VERSION NO:	02		TFT MODULE
		SCALE : 1/1	UNIT: mm
		SHEET NO.: 1/1	

VER.	REVISED DESCRIPTION	REVISER	DATE
02	ADD P/N OF THE DRIVER IC	RITA	2023.03.29
01	FIRST ISSUE	RITA	2023.03.24