


DETAIL A
(SCALE 3:1)



BACKLIGHT CIRCUIT DIAGRAM

PIN DESCRIPTION	
PIN	SYMBOL
1	NC
2	NC
3	NC
4	NC
5	GND
6	VCOM
7	VCC
8	MODE
9	DE
10	VS
11	HS
12	B7
13	B6
14	B5
15	B4
16	B3
17	B2
18	B1
19	B0
20	G7
21	G6
22	G5
23	G4
24	G3
25	G2
26	G1
27	G0
28	R7
29	R6
30	R5
31	R4
32	R3
33	R2
34	R1
35	R0
36	GND
37	DCLK
38	GND
39	L/R
40	U/D
41	VGH
42	VGL
43	AVDD
44	RESET
45	NC
46	VCOM
47	DITHB
48	GND
49	NC
50	NC

NOTES:

1. DISPLAY TYPE: TFT, TRANSMISSIVE, NORMALLY BLACK
2. OPERATING VOLTAGE: VCC=3.3V (TYP.)
3. VIEWING DIRECTION: 12 O'CLOCK
4. DRIVER IC: NT52001 + NT39419B
5. OPERATING TEMP.: -20°C ~ 70°C
6. STORAGE TEMP.: -30°C ~ 80°C
7. LED BACKLIGHT: 27-CHIP WHITE LED, IF=180mA, VF=8.4V~9.9V
8. SURFACE LUMINANCE: 500CD/M² (TYP.)
9. TOP POLARIZER SURFACE TREATMENT: ANTI-GLARE
10. GENERAL TOLERANCE: ±0.3MM
11. ROHS COMPLIANT

02	ADD THE P/N OF DRIVER IC. CORRECT THE PIN ASSIGNMENT OF PIN 1 ~ PIN 4.	RITA	2019.09.06	CHECKED BY:	RITA	2018.06.14	SCALE : 1/1	MODULE P/N:	MI080ACT-1
01	FIRST ISSUE	RITA	2018.06.14	APPROVED BY:			UNIT: mm	DESCRIPTION:	TFT MODULE
VER.	REVISED DESCRIPTION	REVISER	DATE	VERSION NO:	02		SHEET NO.: 1/1		



MULTI-INNO TECHNOLOGY CO., LTD.