



PIN ASSIGNMENT	
NO	SYMBOL
1	LEDK
2	LEDA
3	GND
4	TE
5	LCD_ID
6	RESET
7	IOVCC
8	VDD
9	GND
10	MIPI_D2P
11	MIPI_D2N
12	GND
13	MIPI_D1P
14	MIPI_D1N
15	GND
16	MIPI_CP
17	MIPI_CN
18	GND
19	MIPI_D0P
20	MIPI_D0N
21	GND
22	MIPI_D3P
23	MIPI_D3N
24	GND




DETAIL A
(SCALE 40:1)

NOTES:

1. DISPLAY TYPE: TFT, TRANSMISSIVE, NORMALLY BLACK
2. OPERATING VOLTAGE: VDD=2.8V (TYP.)
3. VIEWING DIRECTION: FULL VIEWING ANGLE
4. DRIVER IC: HX8260
5. OPERATING TEMP.: -20°C ~ 70°C
6. STORAGE TEMP.: -30°C ~ 70°C
7. LED BACKLIGHT: 21-CHIP WHITE LED, IF=81mA, Vf=21.7V±2.1V
8. SURFACE LUMINANCE: 450CD/M² (TYP.)
9. TOP POLARIZER SURFACE TREATMENT: ANTI-GLARE
10. THE SINGLE LAYER AREA OF FPC IS BENDABLE AND THE BENDING RADIUS MUST BE NOT LESS THAN 1.5MM
11. GENERAL TOLERANCE: ±0.3MM
12. ROHS COMPLIANT



BACKLIGHT CIRCUIT DIAGRAM



MULTI-INNO TECHNOLOGY CO., LTD.

DRAWN BY:	RITA	2019.10.23		MODULE P/N:
CHECKED BY:			SCALE : 1/1	MI0800AJT-2
APPROVED BY:			UNIT: mm	DESCRIPTION:
VER.	01	FIRST ISSUE	SHEET NO.: 1/1	TFT MODULE

VER.	01	FIRST ISSUE	RITA	2019.10.23
VER.		REVISED DESCRIPTION	REVISER	DATE