



PIN DESCRIPTION FOR CN2	
PIN	SYMBOL
1	ON/OFF
2	NC
3	NC
4	NC
5	VCC
6	VCC
7	VCC
8	GND
9	RXCLK+
10	RXCLK-
11	RXIN2+
12	RXIN2-
13	RXIN1+
14	RXIN1-
15	RXIN0+
16	RXIN0-
17	NC
18	NC
19	GND
20	GND

PIN DESCRIPTION FOR RTP	
PIN	SYMBOL
1	Y1
2	X1
3	Y2
4	X2



NOTES:

1. DISPLAY TYPE: TFT, TRANSMISSIVE, NORMALLY WHITE
2. OPERATING VOLTAGE: VCC=3.3V (TYP.)
3. VIEWING DIRECTION: 12 O'CLOCK
4. DRIVER IC: -
5. OPERATING TEMP.: -20°C ~ 70°C
6. STORAGE TEMP.: -30°C ~ 80°C
7. LED BACKLIGHT: LED
8. SURFACE LUMINANCE: 200CD/M² (TYP.)
9. TOP POLARIZER SURFACE TREATMENT: ANTI-GLARE
10. CN2 CONNECTOR: A1007WR-S-20P
MATE CONNECTOR: A1007H-20P
11. GENERAL TOLERANCE: ±0.3MM
12. ROHS COMPLIANT

		MULTI-INNO TECHNOLOGY CO., LTD.	
DRAWN BY:	CAROL	2014.11.05	
CHECKED BY:			SCALE : 1/1
APPROVED BY:			UNIT: mm
VERSION NO:	02		SHEET NO.: 1/1
MODULE P/N:			MIO800FT-11
DESCRIPTION:			TFT + RTP MODULE

VER.	REVISED DESCRIPTION	REVISER	DATE
02	MODIFY THE FPC PIN ASSIGNMENT	CAROL	2014.11.17
01	FIRST ISSUE	CAROL	2014.11.05