



- NOTES:
1. DISPLAY TYPE: TFT, TRANSMISSIVE, NORMALLY WHITE
  2. OPERATING VOLTAGE: VDD=3.3V (TYP.)
  3. VIEWING DIRECTION: 6 O'CLOCK
  4. DRIVER IC: HX8264-D03\*2 + HX8677-A00
  5. OPERATING TEMP.: -20°C ~ 70°C
  6. STORAGE TEMP.: -30°C ~ 80°C
  7. LED BACKLIGHT: 42-CHIP WHITE LED, IF=140mA, VF=17.4V~20.4V
  8. SURFACE LUMINANCE: 410CD/M<sup>2</sup> (TYP.)
  9. TOP POLARIZER SURFACE TREATMENT: TBD
  10. CN1:MSB24013P20HA (STM) OR COMPATIBLE  
MATING CONNECTOR: P24013P20 (STM) OR COMPATIBLE.
  11. CN2:3808K-F04N-03R (ENTERY) OR COMPATIBLE  
MATING CONNECTOR: H208K-P04N-02B (ENTERY) OR COMPATIBLE.
  12. GENERAL TOLERANCE: ±0.3MM
  13. ROHS COMPLIANT

PIN DESCRIPTION FOR CN1	
PIN	SYMBOL
1	VDD
2	VDD
3	UD
4	LR
5	RXIN1-
6	RXIN1+
7	GND
8	RXIN2-
9	RXIN2+
10	GND
11	RXIN3-
12	RXIN3+
13	GND
14	RXCLKIN-
15	RXCLKIN+
16	GND
17	NC
18	NC
19	RXIN4-
20	RXIN4+

  

PIN DESCRIPTION FOR CN2	
PIN	SYMBOL
1	VCC
2	GND
3	DISPLAY ON/OFF
4	DIMMING

MULTI-INNO TECHNOLOGY CO., LTD.			
DRAWN BY:	RITA	2018.11.16	MODULE P/N:
CHECKED BY:			MI0840L2T-1
APPROVED BY:			DESCRIPTION:
VERSION NO.:	01		TFT MODULE
		SCALE : 1/1	UNIT: mm
		SHEET NO.: 1/1	

01	FIRST ISSUE	RITA	2018.11.16
VER.	REVISED DESCRIPTION	REVISER	DATE