



PIN DESCRIPTION			
PIN	SYMBOL	PIN	SYMBOL
1	LED+	26	G1
2	LED+	27	G0
3	LED-	28	R7
4	LED-	29	R6
5	GND	30	R5
6	VCOM	31	R4
7	DVDD	32	R3
8	MODE	33	R2
9	DE	34	R1
10	VS	35	R0
11	HS	36	GND
12	B7	37	DCLK
13	B6	38	GND
14	B5	39	L/R
15	B4	40	U/D
16	B3	41	VGH
17	B2	42	VGL
18	B1	43	AVDD
19	B0	44	RESET
20	G7	45	NC
21	G6	46	VCOM
22	G5	47	DITHB
23	G4	48	GND
24	G3	49	NC
25	G2	50	NC

NOTES:

1. DISPLAY TYPE: TFT, TRANSMISSIVE, NORMALLY WHITE
2. OPERATING VOLTAGE: DVDD=3.3V (TYP.)
3. VIEWING DIRECTION: 12 O'CLOCK
4. DRIVER IC: HX8264 + HX8664
5. OPERATING TEMP.: -20°C ~ 70°C
6. STORAGE TEMP.: -30°C ~ 80°C
7. LED BACKLIGHT: 33-CHIP WHITE LED, IF=220mA, VF=9.3V~10.5V
8. SURFACE LUMINANCE: 250CD/M² (TYP.)
9. TOP POLARIZER SURFACE TREATMENT: ANTI-GLARE
10. THE SINGLE LAYER AREA OF FPC IS BENDABLE AND THE BENDING RADIUS MUST BE NOT LESS THAN 1.5MM
11. GENERAL TOLERANCE: ±0.3MM
12. ROHS COMPLIANT

MULTI-INNO TECHNOLOGY CO., LTD.			
DRAWN BY:	CAROL 2009.08.11		MODULE P/N:
CHECKED BY:			SCALE : 1/1
APPROVED BY:		UNIT: mm	DESCRIPTION:
VER.	REVISED DESCRIPTION	SHEET NO.: 1/1	TFT MODULE

01	FIRST ISSUE	CAROL	2009.08.11
VER.	REVISED DESCRIPTION	REVISER	DATE

VERSION NO:	01
-------------	----