



PIN ASSIGNMENT	
1	NC
2	VDD
3	VDD
4	VDD EDID
5	SCL EDID
6	SDA EDID
7	NC
8	LV0N
9	LV0P
10	GND
11	LV1N
12	LV1P
13	GND
14	LV2N
15	LV2P
16	GND
17	LVCLKN
18	LVCLKP
19	GND
20	LV3N
21	LV3P
22	GND
23	LED GND
24	LED GND
25	LED GND
26	NC
27	LED PWM
28	LED EN
29	NC
30	NC
31	LED VCC
32	LED VCC
33	LED VCC
34	NC
35	BIST
36	NC
37	NC
38	NC
39	NC
40	NC

NOTES:

1. DISPLAY TYPE:TFT, TRANSMISSIVE, NORMALLY BLACK.
2. OPERATING VOLTAGE: VDD=3.3V.
3. VIEWING DIRECTION: FULL VIEWING ANGLE.
4. DRIVER IC: TBD.
5. OPERATING TEMP.: -20°~70°.
6. STORAGE TEMP.: -30°~80°.
7. LED BACKLIGHT: LED.
8. SURFACE LUMINANCE: 350cd/m<sup>2</sup>(TYP.).
9. TREATMENT OF TOP SURFACE: GLARE.
10. GENERAL TOLERANCE: ±0.2.
11. RoHS COMPLIANT.



MULTI-INNO TECHNOLOGY CO., LTD.

DRAWN BY:	RITA	2017.04.12	SCALE : 1/1	MODULE P/N:
CHECKED BY:			UNIT:	MI1010ADT-1
APPROVED BY:			mm	DESCRIPTION:
VERSION NO:	01			TFT MODULE

VER.	REVISED DESCRIPTION	REVISER	DATE
01	First issue	RITA	2017.04.12