



24-LED WHITE 200MA/9.6V

NOTES:

1. DISPLAY TYPE: TFT, TRANSMISSIVE, NORMALLY WHITE.
2. OPERATING VOLTAGE: DVDD=3.3V.
3. VIEWING DIRECTION: 12 O'CLOCK.
4. IC DRIVER: HX8282+HX8696.
5. OPERATING TEMP: -20°C ~ 70°C.
6. STORAGE TEMP: -30°C ~ 80°C.
7. LED BACKLIGHT: 24-CHIP WHITE LED, If=200mA, Vf=9.6V.
8. SURFACE LUMINANCE: 350CD/M<sup>2</sup>(TYP.).
9. TOP POLARIZER SURFACE TREATMENT: ANTI-GLARE.
10. GENERAL TOLERANCE: ±0.3mm.
11. RoHS COMPLIANT.

PIN ASSIGNMENT

Pin	SYMBOL
1	NC
2	NC
3	NC
4	NC
5	GND
6	VCOM
7	DVDD
8	MODE
9	DE
10	VS
11	HS
12	B7
13	B6
14	B5
15	B4
16	B3
17	B2
18	B1
19	B0
20	G7
21	G6
22	G5
23	G4
24	G3
25	G2
26	G1
27	G0
28	R7
29	R6
30	R5
31	R4
32	R3
33	R2
34	R1
35	R0
36	GND
37	DCLK
38	GND
39	L/R
40	U/D
41	VGH
42	VGL
43	AVDD
44	RESET
45	NC
46	VCOM
47	DITHB
48	GND
49	NC
50	NC



MULTI-INNO TECHNOLOGY CO.,LTD.

DRAWN BY:	RITA	2019.06.17		MODULE P/N:	MI101021T-4
CHECKED BY:			SCALE :	1/1	
APPROVED BY:			UNIT:	mm	DESCRIPTION:
VERSION NO.:	02		SHEET NO.:	1/1	TFT MODULE

VER.	REVISED DESCRIPTION	REVISER	DATE
02	CORRECT THE FPC LENGTH.	RITA	2019.11.26
01	FIRST ISSUE	RITA	2019.06.17