



"A"---Dots Detail
scale 10X

FPC Pin Assignment

1	NC
2	VSS
3	VSS
4	NC
5	VDD
6	IM1
7	IM2
8	CSB
9	RESB
10	A0
11	WRB
12	RDB
13	DO
14	D1
15	D2
16	D3
17	D4
18	D5
19	D6
20	D7
21	IREF
22	VCOMH
23	VPP
24	NC

- NOTES:
1. OPERATING TEMP:-30° C TO 80° C
 2. STORAGE TEMP: -40° C TO 85° C
 3. VIEWING DIRECTION:ALL
 4. OLED DRIVE IC:SH1107
 5. DISPLAY COLOR:YELLOW
 6. UNSPECIFIED TOLERANCES: ± 0.2mm.
 7. () MEANS: DIMENSION FOR REFERENCE
 8. THE PROTECTIVE FILM ON FRONT SIDE OF OLED MUST BE REMOVED BEFORE ASSEMBLY BY CUSTOMER (客户在装机时, 自己必须撕掉保护膜)

MULTI-INNO TECHNOLOGY CO.,LTD.		
DRAWN BY: CAROL 2015.10.30	SCALE: 1/1	MODULE P/N:
CHECKED BY:	UNIT: mm	MI128128LO-Y
APPROVED BY:	VERSION NO: 01	DESCRIPTION:
VER. REVISED DESCRIPTION	DATE	OLED MODULE