



Pin Assignment
NO. SYMBOL

1	VCC
2	NC
3	VCOMH
4	VDD
5	VCI
6	IREF
7	CSB
8	RESB
9	A0
10	SCLK
11	SDIN
12	VSS

- NOTES:
1. OPERATING TEMP: -30° C TO 70 ° C
 2. STORAGE TEMP: -40° C TO 80 ° C
 3. VIEWING DIRECTION: ALL
 4. OLED DRIVE IC: SSD1327
 5. DISPLAY COLOR: White
 6. UNSPECIFIED TOLERANCES: ± 0.2mm.
 7. () MEANS: DIMENSION FOR REFERENCE
 8. THE PROTECTIVE FILM ON FRONT SIDE OF OLED MUST BE REMOVED BEFORE ASSEMBLY BY CUSTOMER (客户在装机时, 自己必须撕掉保护膜)



MULTI-INNO TECHNOLOGY CO., LTD.

DRAWN BY:	RITA 2016.05.27	SCALE : 1/1	MODULE P/N:
CHECKED BY:		UNIT: mm	MI128128MO-W
APPROVED BY:			DESCRIPTION:
VERSION NO:	01		OLED MOUDLE

01	FIRST ISSUE	2016.05.27
VER.	REVISED DESCRIPTION	DATE