



PIN DESCRIPTION	
PIN	SYMBOL
1	NC
2	VSS
3	SW
4	VDD2
5	FB
6	SENSE
7	VBREF
8	VDD1
9	C86
10	P/S
11	/CS
12	/RES
13	A0
14	/WR
15	/RD
16	VCOMH
17	VPP
18	DO
19	D1
20	D2
21	D3
22	D4
23	D5
24	D6
25	D7
26	IREF
27	NC

NOTES:

- COLOR: WHITE
- OPERATING VOLTAGE: VPP=8.0V (TYP.)
- DRIVE DUTY: 1/32
- DRIVER IC: SHM6211
- OPERATING TEMP.: -40°C ~ 70°C
- STORAGE TEMP.: -40°C ~ 85°C
- INTERFACE: 8-BIT 6800/8080 PARALLEL, SPI, IIC
- ONLY THE SINGLE LAYER AREA ON FPC IS BENDABLE AND THE MINIMUM BEND RADIUS IS 1.5MM
- GENERAL TOLERANCE: ±0.3MM
- ROHS COMPLIANT



MULTI-INNO TECHNOLOGY CO., LTD.

DRAWN BY:	CAROL	2014.02.19		MODULE P/N:
CHECKED BY:			SCALE : 1/1	M12832J0-W1
APPROVED BY:			UNIT: mm	DESCRIPTION:
VERSION NO:	01		SHEET NO.: 1/1	OLED MODULE

01	FIRST ISSUE	CAROL	2014.02.19
VER.	REVISED DESCRIPTION	REVISER	DATE