


COM&SEG LAYOUT



Detail A (20:1)

Pin Assignment	
NO.	SYMBOL
1	C2P
2	C2N
3	C1P
4	C1N
5	VBAT
6	VSS
7	VDD
8	RES#
9	SA0
10	SCLK
11	SDA
12	VCOMH
13	VCC

SA0	I <sup>2</sup> C address
0	0x78
1	0x7a

Specification

1. Display: OLED(White)
2. Format: 128\*32
3. Driver IC: SSD1306BZ
4. General Tolerance:  $\pm 0.3$
5. Operate temp. :  $-40^{\circ}\text{C} \sim 70^{\circ}\text{C}$   
Storage temp. :  $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$
6. DUTY: 1/32
7. RoHS Compliant



MULTI-INNO TECHNOLOGY CO., LTD

DRAWN BY:	RITA	2016.06.22	SCALE : 1/1	MODULE P/N:
CHECKED BY:			UNIT:	MI12832R0-W
APPROVED BY:			mm	DESCRIPTION:
VERSION NO:	01			OLED MODULE

01	FIRST ISSUE	RITA	2016.06.22
VER.	REVISED DESCRIPTION	REVISER	DATE