



PIN ASSIGNMENT	
PIN	SYMBOL
1	C2P
2	C2N
3	C1P
4	C1N
5	VBAT
6	VBREF
7	VSS
8	VDD
9	RES#
10	SCL
11	SDA
12	IREF
13	VCOMH
14	VCC

NOTES:

- COLOR: WHITE
- OPERATING VOLTAGE: VDD1=2.8V (TYP.)
- DRIVE DUTY: 1/32
- DRIVER IC: CH1115
- OPERATING TEMP.: -40°C ~ 85°C
- STORAGE TEMP.: -40°C ~ 85°C
- INTERFACE: I²C
- GENERAL TOLERANCE: ±0.3MM
- ROHS COMPLIANT

01	FIRST ISSUE	RITA	2021.06.09	APPROVED BY:		UNIT: mm	DESCRIPTION:
VER.	REVISED DESCRIPTION	REVISER	DATE	VERSION NO:	01	SHEET NO.: 1/1	OLED MODULE


MULTI-INNO TECHNOLOGY CO., LTD.
 DRAWN BY: RITA 2021.06.09  MODULE P/N:
 CHECKED BY: SCALE : 1/1 MI12832WO-W
 APPROVED BY: UNIT: mm DESCRIPTION:
 VERSION NO: 01 SHEET NO.: 1/1 OLED MODULE