



Pin	Symbol
1	N.C. (GND)
2	VCC
3	VCOMH
4	IREF
5	D7
6	D6
7	D5
8	D4
9	D3
10	D2
11	D1
12	D0
13	E/RD#
14	R/W#
15	DC#
16	RES#
17	CS#
18	N.C.
19	BS2
20	BS1
21	VDD
22	N.C.
23	N.C.
24	N.C.
25	N.C.
26	N.C.
27	N.C.
28	N.C.
29	VSS
30	VSL

NOTES:

- COLOR: WHITE (16 GRAY SCALES)
- OPERATING VOLTAGE: VDD=2.8V (TYP.)
- DRIVE DUTY: 1/64
- DRIVER IC: SSD1325
- OPERATING TEMP.: -40°C ~ 70°C
- STORAGE TEMP.: -40°C ~ 85°C
- INTERFACE: 8-BIT 68XX/80XX PARALLEL, 4-WIRE SPI
- THE TOTAL THICKNESS (2.10 MAX.) IS WITHOUT POLARIZER PROTECTIVE FILM, REMOVE TAPE & DRIVER IC.
THE ACTUAL ASSEMBLED TOTAL THICKNESS WITH ABOVE MATERIALS SHOULD BE 3.15 MAX.
- GENERAL TOLERANCE: ±0.3MM
- ROHS COMPLIANT

MULTI-INNO TECHNOLOGY CO., LTD.

DRAWN BY:	RITA	2023.02.10		MODULE P/N:
CHECKED BY:			SCALE : 1/1	MI12864A10-W
APPROVED BY:			UNIT: mm	DESCRIPTION:
VERSION NO:	01		SHEET NO.: 1/1	OLED MODULE

01	FIRST ISSUE	RITA	2023.02.10
VER.	REVISED DESCRIPTION	REVISER	DATE